


Type :

Project :

Catalog # :

FEATURE(S):



SPECIFICATION

Ceiling cut-out: 5 3/4"

12V Out 50W Max

Application: General purpose recessed downlight housing for medium to high ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the proper décor and illumination.

Housing: Pre-wired housing adjusts up to a 1 1/2" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Trim is secured with torsion wing springs/standard coil springs.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Transformer: Class H insulated magnetic transformer installed adjacent to Junction Box, bottom and top accessible. Thermally protected rated for 90° C

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box: 16 gauge pre-wired galvanized steel Junction Box, 25 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (5) 3/4", (1) 1" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: IC rated housing rated for direct contact with low to medium density loosefill blown and rolled insulation. For use with high density loosefill blown insulation, reduce rated lamp wattage accordingly (roughly %15-%20).

Airflow: Airtight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: U.L. Listed, E.T.L. Listed

COMPATIBILITY

 LR1503 ADJUSTABLE GIMBAL W/ BAFFLE	 LR1520 ADJUSTABLE SPOT W/ BAFFLE	 LR1557 SUPER ADJUSTABLE PULL DOWN
 LR1567 ADJUSTABLE PULL DOWN	 LR1588 ADJUSTABLE SPOT	 LR1598 ADJUSTABLE EYEBALL W/ BAFFLE

Note: Wattage limitations on compatible items must be met.

ORDERING

ORDERING EXAMPLE : LH1599ICA

LH1599IC	RATING	WATTAGE	VOLTAGE*	ACCESSORIES
LH1599IC	A :IC-Airtight	Blank:50W	Blank:120V/12V -27 :277V/12V (Electronic*)	/LBL20 :20W Derating /LBL35 :35W Derating

* Available with 120V/277V Magnetic Option, consult factory.