

## LH2R - REMODEL 2" LINE VOLTAGE DOWNLIGHT



### PROJECT INFORMATION

Type :

Project :

Catalog # :

### FEATURE(S):



### SPECIFICATION

*Ceiling cut-out: 2 5/8"*

120V 50W MR16 GU10

**Application:** General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

**Housing:** Pre-wired .05" baked enamel 1-piece drawn steel housing adjusts up to 1-1/4" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Trim is secured with torsion wing springs.

**Mounting:** Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheet rock ceiling for fast and easy installation.

**Socket:** Standard porcelain GU10 "Twist & Lock" socket with high temperature leads.

**Junction Box:** 16 gauge pre-wired aluminum Junction Box, suitable for through branch wiring for a maximum of (4) #12 AWG wires. Furnished with (2) 3/4" knock-outs. Screw-in or out covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

**Safety Labels:** ETL/CETL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

**Label:** E.T.L. Listed

### COMPATIBILITY



[LR1203](#)

CROSS BLADE



[LR1221](#)

MR16 REFLECTOR



[LR1293](#)

MR16 BAFFLE

Note: Wattage limitations on compatible items must be met.