




PROJECT INFORMATION

Type :

Project :

Catalog # :

FEATURE(S):



SPECIFICATION

Ceiling cut-out: 4 1/2"

120V 75W Max PAR20/PAR30 MED E26
40W A19

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired housing adjusts up to 1 1/4" ceiling thickness. This housing has torsion remodeling clips for secure installation. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out (above ceiling access is not required).

Mounting: Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheet rock ceiling for fast and easy installation.

Socket: Standard porcelain medium screw base socket with high temperature leads.

Junction Box: 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (6) 3/4" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non IC rated housing must be kept 3" from insulation.

Airflow: Airtight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: U.L. Listed, E.T.L. Listed

COMPATIBILITY

 LR43 PAR30 WET LOCATION TRIM	 LR987 ADJUSTABLE REFLECTOR	 LR993 PHENOLIC BAFFLE
 LR994 DEEP PHENOLIC BAFFLE	 LR999 SHALLOW REFLECTOR	 LRD400 4" 120V LOW PROFILE L.E.D. TRIM RETROFIT
 LRD400 4" 12V L.E.D. RETROFIT LOW PROFILE TRIM	 LRD402 4" 120V BASIC REFLECTOR RETROFIT (NON-DIMMING)	 LRD442 4" 120V DECO DOME RETROFIT (NON-DIMMING)
 LRM985 ADJUSTABLE METAL BAFFLE	 LRM993 METAL BAFFLE	

Note: Wattage limitations on compatible items must be met.

ORDERING

ORDERING EXAMPLE : LH99R

LH99R	RATING
LH99R	Blank: Standard
A	: Airtight