

LR1419 - PINHOLE W/ PHENOLIC BAFFLE

4" LINE VOLTAGE GU10 TRIMS





PROJECT INFORMATION

Type :

Project :

Catalog # :



Not Compatible w/ Shallow Housings

FEATURE(S):



SPECIFICATION

120V 50W Max MR16 GU10

Application: These narrow aperture beams allow a defined location to be lit without affecting the surrounding surfaces while concealing the lamp image and providing a consistent ceiling appearance. The smaller the aperture the more confined the illumination. **Pinhole** trims provide the type of precise illumination needed for artwork such as paintings and statues. They are also ideal for cozy environments like restaurants and living spaces where glare-free illumination is desired. Aside from accent lighting, they can also be utilized for task lighting applications such as above tables, workspace, cabinetry, and other locations where a directed beam is desired.

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.

Lens Inclusion: Clear glass protective safety lens included in packaging.

Mounting Steel pressure springs mounted on trim to ensure positive retention inside housing.

Baffle Finish *: Molded baffle ridges eliminate stray light. Available in White, Black and All Mocha.

Ring Finish: Die-Cast Aluminum Trim Ring Available in White, Black, Natural and Mocha.

Accessories: Takes (1) 2" Media.

Label: U.L. Listed, E.T.L. Listed

COMPATIBILITY



LH99-GU10

NEW CONSTRUCTION



LH99ICA-GU10

IC HOUSING



LH99R-GU10

REMODEL

Note: Wattage limitations on compatible items must be met.

ORDERING

ORDERING EXAMPLE : LR1419W

LR1419	BAFFLE FINISH *	RING FINISH	ACCESSORIES
LR1419	W :White	Blank :White	/L38 :Clear Lens
	B :Black	B :Black	/L39 :Red Lens
	MO :All Mocha	N :Natural	/L40 :Yellow Lens
		MO :Mocha	/L41 :Blue Lens
			/L42 :Amber Lens
			/L43 :Green Lens
			/L44 :Daylight Blue Lens
			/L48 :Lens with Internal Louver Filter
			/L49 :Frosted Soft Focus
			/L50UV :UltraViolet Filter
			/L53 :Micro - Prismatic Spread Lens
			/L54 :Micro - Prismatic Spread Lens (Light Diffuse)
			/L55 :Linear Spread Lens
			/LL16B :Black
			/LL16C :Clear
			/LL16HD-B :Heavy Duty Black
			/LL16HD-C :Heavy Duty Clear

* Finishes designated with "ALL" prior to the finish color come standard with a matching ring finish. Use "W" for White Ring.