

LSH1499R - SHALLOW REMODEL HOUSING

4" LOW VOLTAGE HOUSINGS




PROJECT INFORMATION

Type :

Project :

Catalog # :

FEATURE(S):



SPECIFICATION

Ceiling cut-out: 4 1/4"

12V Out 37W Max MR16

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired housing adjusts up to 1 1/4" ceiling thickness. This housing has torsion remodeling clips for secure installation. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out (above ceiling access is not required).

Mounting: Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheet rock ceiling for fast and easy installation.

Transformer: Class 2 Noise-Free Electronic transformer installed adjacent to Junction Box, bottom and top accessible. Thermally protected rated for 90° C

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.
















Junction Box: 16 gauge pre-wired aluminum Junction Box, suitable for through branch wiring for a maximum of (4) #12 AWG wires. Furnished with (2) 3/4" knock-outs. Screw-in or out covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non IC rated housing must be kept 3" from insulation.

Safety Labels: ETL/CETL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: E.T.L. Listed

COMPATIBILITY

 LR1401 CLEAR LENSED REFLECTOR	 LR1403 BAFFLE W/ CLEAR LENS	 LR1409 ADJUSTABLE GIMBAL
 LR1421 REFLECTOR	 LR1423 FROSTED GLASS DOME	 LR1424 SHOWER DECO GLASS (FROSTED RING)
 LR1431 DECO SHIELD REFLECTOR	 LR1433 DECO SHIELD BAFFLE	 LR1435 ADJUSTABLE SPOT
 LR1438 REGRESSED EYEBALL	 LR1443 PINHOLE W/ BAFFLE	 LR1444 NARROW APERTURE REFLECTOR
 LR1445 WALL WASH REFLECTOR EYELID	 LR1450 DECO GLASS PANEL	 LR1461 PINHOLE W/ REFLECTOR

Please see website for more compatible items.

Note: Wattage limitations on compatible items must be met.

ORDERING

ORDERING EXAMPLE : LSH1499RE

LSH1499R	RATING	WATTAGE	VOLTAGE*	OPTION	ACCESSORIES
LSH1499R	E :Electronic	Blank :37W	Blank :120V -27 :277V (Electronic*)	Blank :None	/LBL20 :20W Derating /LBL35 :35W Derating

* Available with 120V/277V Magnetic Option, consult factory.