

# LITON LED MINIATURE STEP & PATHWAY

MINIATURE STEP & PATHWAY LED LIGHTING



## Applications:

LITON LED Step and Pathway lights are an energy efficient solution for lighting interior pathways, aisles and low-level points of egress in residential and commercial applications. Perfect for improving safety on stairways, ramps and other dimly lit areas.

6 SLEEK SHAPES  
STEP & PATHWAY  
LED LIGHTING



## Product Benefits:

- 6 stylish trim options: vertical, horizontal, round, open lens and louvered.
- High quality, die-cast step lights feature a 'no-screw' faceplate for a sleek, modern appearance.
- Energy Efficient: 3.5 watts delivers 240Lm
- Easy to install, direct 120V wiring, no remote drivers
- Mounts to standard 4" J-box. ELV dimming standard.

# LED STEPLIGHTS / PATHWAY LIGHTS

FOR ILLUMINATING PATHWAYS, STAIRCASES, AISLES AND LOW LEVEL POINT OF EGRESS

# LITON®

High quality, die-cast step lights feature a 'no-screw' faceplate for a sleek, modern appearance. Consuming only 3.5 watts and delivering 240Lm, they are an energy efficient solution for lighting interior pathways, aisles and low-level points of egress in residential and commercial applications. Perfect for improving safety in dimly lit areas.

## FEATURES

No-Screw Faceplate for a clean modern look

Energy efficient, consumes just 3.5 watts, delivers 240 Lumens

Mounts to standard Single-Gang J-Box (1-1/2" Minimum Depth)

120V direct wiring. No remote driver required

3,000K CCT, 80CRI

Available with Amber Lens (~590nm)

ELV dimming is standard. Dims to 10%

Horizontal

Seamless die-cast aluminum construction for durability and long lasting beauty


Round Models offer Optional Mounting Bracket for cement pour, retrofit and joist mount. **(LSLDR-BRKT)**

Round

Vertical


FOR ILLUMINATING PATHWAYS, STAIRCASES, AISLES AND LOW LEVEL POINT OF EGRESS

## ▶ Vertical Open Lens




CAT#	FINISH	LENS
LSLD00	W: All White	Blank: 3000K
	B: All Black	-TAM: Amber (~590nm)

## ▶ Vertical Louver




CAT#	FINISH	LENS
LSLD73	WW: All White	Blank: 3000K
	BB: All Black	-TAM: Amber (~590nm)

## ▶ Open Lens Rectangle




CAT#	FINISH	LENS
LSLDH00	W: All White	Blank: 3000K
	B: All Black	-TAM: Amber (~590nm)

## ▶ Rectangle Louver




CAT#	FINISH	LENS
LSLDH73	WW: All White	Blank: 3000K
	BB: All Black	-TAM: Amber (~590nm)

## ▶ Open Lens Round\*



CAT#	FINISH	LENS
LSLDR00	W: All White	Blank: 3000K
	B: All Black	-TAM: Amber (~590nm)

## ▶ Round Louver\*



CAT#	FINISH	LENS
LSLDR73	WW: All White	Blank: 3000K
	BB: All Black	-TAM: Amber (~590nm)

\* Round Models offer Optional Mounting Bracket for cement pour, retrofit and joist mount. (LSLDR-BRKT)

