

DLCT-SERIES

CATENARY DOWNLIGHT

Litcon®
OUTDOOR



Wall Mount Emergency System (-EMB) feature

Catenary Downlight

Designed for outdoor settings that need direct control of light, LITON's Catenary Mounting System supports the installation of DL luminaires and their required wiring on a catenary cable. Catenary cables, fittings and other structural elements provided by others.

BENEFITS

- 1000lm-2600lm (10W-30W)
- Direct (DM), Pendant (PD), Adjustable (AJ) or 6"- 36" Stem (ST)
- 3 and 5 Conductor Power Cord ordered separately
- Emergency & RGBW options


Available Luminaires



DLCT340-ADJ
4" Round Adjustable
1000lm-1500lm
(10W-15W)
RMT or SDL

DLCTQ340-PD
4" Square Pendant
1000lm-1500lm
(10W-15W)
RMT or SDL

DLCT360-DM
6" Round Direct
1000lm-2600lm
(10W-30W)
RMT or SDL



SDL (Integral Daylight)



RMT (Remote Motion/Daylight)

Options



Optional Frosted Lens feature




Optional Hex-Cell Louver feature



Optional Glare Shield feature

STANDARD BEAMS



10° 20° 45° 60°

SPECIALTY BEAMS



30°x60°



STANDARD FINISHES



White Silver Bronze Black

SPECIAL ORDER FINISHES



Light Silver Dark Gray Metallic Gold Metallic Black



RGBW Option



Emergency Backup



US Assembled



120V



277V



347V Option



Dark Sky Option



Tamper Resistant



LINK TO WEB PAGE