


LH1499R - REMODEL HOUSING 120V/277V

4" LOW VOLTAGE HOUSINGS



SPECIFICATION

12V Out 75W Max MR16
Ceiling Cut Out: 4 1/4"

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired housing adjusts up to 1 1/4" ceiling thickness. This housing has torsion remodeling clips for secure installation. Integral thermal protector to guard against improper lamping and installation. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out (above ceiling access is not required).

Mounting: Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

Transformer: Class H insulated magnetic transformer installed adjacent to Junction Box, bottom and top accessible. Thermally protected rated for 90° C

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box: 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with 3/4", 1" and Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.
















Insulation Contact: Non-IC rated housing must be kept 3" from insulation.

Airflow: Airtight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: UL Listed, cETL Listed

COMPATIBILITY

 LR1409 ADJUSTABLE GIMBAL	 LR1420 ADJUSTABLE SLOT	 LR1446 DECO GLASS-SHIELD (DOME)
 LR1467 ADJUSTABLE PULL DOWN	 LR1471 ADJUSTABLE WALL WASH REFLECTOR	 LRQ1481 SQUARE RING PULL DOWN
 LR1421 REFLECTOR	 LR1477 PINHOLE W/ MESH	 LR1461 PINHOLE W/ REFLECTOR
 LR1473 WALL WASH BAFFLE SCOOP	 LR1495 WALL WASH BAFFLE	 LR1498 EYEBALL
 LRQ1493 SQUARE RING BAFFLE	 LR1468 MULTI ACCESSORY PULL DOWN	 LR1435 ADJUSTABLE SPOT

Please see website for more compatible items.

FEATURE:



ORDERING EXAMPLE : LH1499R

LH1499R	RATING	WATTAGEVOLTAGE	ACCESSORIES
LH1499R	Blank :Standard A :Airtight	Blank :50W Magnetic (120V) -75 :75W Magnetic (120V) E-27 :50W Electronic (277V) E :50W Electronic (120V)	/LBL20 :20W Derating /LBL35 :35W Derating

* 75W Housing is 6 3/8" tall
Available with 120V/277V Magnetic Option, consult factory

ID#: 193