


## LH600 - ARCHITECTURAL HOUSING

### 6" ARCHITECTURAL INCANDESCENT HOUSINGS



#### SPECIFICATION

120V 150W Max PAR30/A19/ A21 MED E26

**Application:** Architectural-grade recessed downlight housing for low to medium height ceilings and commercial installations. A variety of trims, compatible styles and finishes are available to achieve the proper décor and illumination.

**Housing Frame:** 16 gauge galvanized plaster ring with powder coat finish, six friction clips secure trim to housing for ceilings up to 1 1/2" thick. Triple slot bat-wing hanger brackets accommodate multiple bar hanger systems.

**Mounting:** Housing suitable for new construction installations only, Bat-Wing bar hanger brackets adjust vertically 3 1/4" for multiple ceiling types and accepts 1/2" EMT, 26" C-Channel Strut for T-bar ceilings and 27" adjustable linear hanger bars for plaster ceilings or wood/metal joists. Heavy duty 16-gauge, die-formed galvanized steel. Bar hangers optional.

**Socket Cap:** Extruded aluminum socket cap, 1 1/4" vertically adjustable socket arm with set screw which enables the use of multiple lamp types and repositioning to optimize lamp performance. Furnished with heat sink fins to vent lamp heat and extend lamp life. Accepts compatible reflector trims.

**Socket:** Standard porcelain medium screw base socket with high temperature leads.

**Junction Box:** 16 gauge pre-wired galvanized steel double Junction Box, 64 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (10) 3/4", (2) 1" and (8) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard die-cast aluminum fitting for flex-conduit.

**Insulation Contact:** Non-IC rated housing must be kept 3" from insulation.












**Safety Labels:** UL/CUL listed for through-branch wiring (16) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

**Warranty:** Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship.

**Label:** UL Listed, cETL Listed

Assembled in USA

#### COMPATIBILITY

 <b><a href="#">LR676</a></b> REFLECTOR W/ GLASS ACCENT	 <b><a href="#">LR673</a></b> BAFFLED REFLECTOR	 <b><a href="#">L270</a></b> LINEAR HANGER BAR SET
 <b><a href="#">LR671</a></b> REFLECTOR	 <b><a href="#">C260</a></b> C-CHANNEL HANGER BAR SET	 <b><a href="#">LR6071</a></b> REFLECTOR W/GLASS RING
 <b><a href="#">LR674</a></b> BAFFLE W/ PRISMATIC LENS	 <b><a href="#">C260-J</a></b> ADJUSTABLE C- CHANNEL HANGER BAR SET	 <b><a href="#">LR672</a></b> REFLECTOR W/ LENS
 <b>C6TR6L</b> 6" COMMERCIAL LED RETROFIT	 <b>C6TR6L</b> 6" COMMERCIAL LED RETROFIT AMBER	

Note: Wattage limitations on compatible items must be met.

#### FEATURE:



ORDERING EXAMPLE : LH600

LH600	WATTAGE	OPTIONS
LH600	Blank :150W	Blank :None
	-FS	:Fuse

ID#: 549