


LHR1399 - REMOTE HOUSING

3" LOW VOLTAGE HOUSINGS



SPECIFICATION

12V In 50W Max MR16

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired housing adjusts up to a 1 1/4" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Remote Transformer: Pre-wired .05" baked enamel 1-piece drawn steel housing adjusts up to 1-1/4" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Trim is secured with torsion wing springs.

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box : 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (7) 3/4" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.
















Insulation Contact: Non-IC rated housing must be kept 3" from insulation.

Airflow: Airtight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: cETL Listed

COMPATIBILITY

 LR1316 DECO GLASS DOME	 LR1381 PULL DOWN ADJUSTABLE REFLECTOR	 LR1320 SLOT
 LR1383 PULL DOWN ADJUSTABLE BAFFLE	 LR1387 DECORATIVE PULL DOWN	 LR1303 CROSS BLADE
 LR1342 REFLECTOR W/ FROSTED LENS (MR16)	 LR1380 PULL DOWN W/ SNOOT	 LR1388 ADJUSTABLE GIMBAL
 LR1396 T4 PULL DOWN	 LR1321 REFLECTOR	 LR1352 DECO GLASS PANEL
 LR1397 MR16 PULL DOWN	 LR1317 REFLECTOR W/ FROSTED LENS (T LAMP)	 LR1319 PINHOLE W/ REFLECTOR

Please see website for more compatible items.

FEATURE:



LHR1399	RATING	WATTAGE
LHR1399	Blank :Standard A :Airtight	Blank :50W

ORDERING EXAMPLE : LHR1399

ID#: 1989

Note: Wattage limitations on compatible items must be met.