


**TYPE** CATALOG#

## **LR2691 - REFLECTOR W/ NARROW APERTURE**

**6" LOW VOLTAGE TRIMS** 







## **SPECIFICATION**

12V 75W Max MR16 GU5.3

Application: Great for basic area lighting of a room or space, accommodating the type of lighting required to enhance its mood and decor. Narrow Aperture trims are best used when maximum lamp cut-off is desired to maximize a glare-free environment. Perfect for "Task Lighting" where a concentrated beam of light is needed to supplement surrounding light for a more effective work environment.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside

Reflector Finish: Spun Aluminum Reflector Available in White, Black, Clear, Gold, All Copper\* and Satin Haze.

Ring Finish: Die-Formed Aluminum Trim Ring Available in White, Black, Natural and Copper.

## COMPATIBILITY



STANDARD HOUSING

120V/277V

<u>LH7LV</u>

**LH7LVIC** IC HOUSING



**LK50** 

MR16 RETROFIT TRANSFORMER

Note: Wattage limitations on compatible items must be met.

**FEATURE:** 









**ORDERING EXAMPLE: LR2691W** 

LR2691	REF	LECTOR FINISH	RING	FINISH		ACCESSORIES
LR2691	W	:White	Blank	:White	/L38	:Clear Lens
	В	:Black		:Black	/L40	:Yellow Lens
	C	:Clear	N	:Natural		:Blue Lens
		:Gold	CO	:Copper	/L42	:Amber Lens
	CO	:All Copper*			/L43	:Green Lens
	S	:Satin Haze			/L44	:Daylight Blue Lens :Lens with Internal Louver Filter
					/L48	:Lens with Internal Louver Filter
						:Frosted Soft Focus
					/L50UV	:UltraViolet Filter
					/L53	:Micro - Prismatic Spread Lens
					/L55	:Linear Spread Lens
					/LL16B	
					/LL16C	:Clear

\* Comes standard with a matching ring finish. Use "W" for White Ring.

eema

ID#: 154