



LRLDH319 - 3" MICRO-CAST PINHOLE 3" LED TRIMS (8W)



SPECIFICATION

8W LED

Application: This miniature general purpose LED Pinhole trim is perfect for low to medium height ceilings in residential and light commercial applications. Its small aperture makes it ideal for strategic placement when tight beam spread control is required and energy savings is important. A variety of finishes and beam spreads are available to achieve a desired look.

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.

Power Connection: LED heat sinked lamp module is replaceable via onboard quick exclusionary disconnect terminal. No tools required. Meets CA Title 24 Requirements and other standards restricting the use of Medium Base or Bi-Pin Sockets.

Lumen Maintenance: Minimum 35,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, finned heat sink design for maximum heat rejection to provide long LED life.

Color Temperature: Comes standard with 3,000K Warm White LED's binned according to ANSI C78 377A for color temperature and chromaticity ranges. Available with 4,000K. To order use "-T" Suffix followed by color temperature. Example 4000K= T40. Consult factory as extended lead times and minimum order quantities apply.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.


Finish: Die-cast aluminum Ring. Available in White, Black, Natural, Copper and Mocha.

Beam Spread: Only available in Narrow Flood.

Label: cETL Listed


Assembled in USA

COMPATIBILITY




LHFRLD3

3" FIRE-RATED LED HOUSING



LHLDH3

LED NEW CONSTRUCTION HOUSING



LHLDH3R

LED REMODEL HOUSING

Note: Wattage limitations on compatible items must be met.

LED Details:

8W 420 + Lumens Delivered
Color Rendering Index (CRI): 90
Color Temperature: 3,000K
Lamp Equivalents: 50W MR16

Benefit:

- Up to 420 Lumens Delivered!
- Budget Friendly, specification quality performance
- Small aperture for hard to light spaces
- Singular diode, no multiple LEDs
- 90CRI standard for better color rendering

2016.9.7

FEATURE:



ORDERING EXAMPLE : LRLDH319BW-B25-WL

LRLDH319	FINISH	BEAM SPREAD	OPTIONS
LRLDH319	BW :White BB :Black BN :Natural BCO :Copper BMO :Mocha	-B25 :Narrow Flood	-WL :Wet Location

ID#: 2296

