



LSH1399 - SHALLOW HOUSING

3" LOW VOLTAGE HOUSINGS



SPECIFICATION

12V Out 37W Max MR16

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired housing adjusts up to a 1 1/4" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Transformer: High quality insulated transformer installed adjacent to Junction Box. Thermally protected rated for 90° C. Available in magnetic or "noise-free" electronic. Magnetic transformer not accessible from below ceiling.

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.
















Junction Box: 16 gauge pre-wired galvanized steel Junction Box, 25 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (3) 3/4", (1) 1" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non-IC rated housing must be kept 3" from insulation.

Safety Labels: ETL/CETL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: cETL Listed

COMPATIBILITY

 LR1311 LOUVER	 LR1317 REFLECTOR W/ FROSTED LENS (T LAMP)	 LR1383 PULL DOWN ADJUSTABLE BAFFLE
 LR1387 DECORATIVE PULL DOWN	 LFB2012 FIRE BARRIER	 LR1356 DECO GLASS
 LR1303 CROSS BLADE	 LR1342 REFLECTOR W/ FROSTED LENS (MR16)	 LR1380 PULL DOWN W/ SNOOT
 LR1388 ADJUSTABLE GIMBAL	 LR1396 T4 PULL DOWN	 LR1321 REFLECTOR
 LR1352 DECO GLASS PANEL	 LR1397 MR16 PULL DOWN	 LSH1399 SHALLOW HOUSING

Please see website for more compatible items.

FEATURE:



LSH1399	RATING	WATTAGE	VOLTAGE	ACCESSORIES
LSH1399	Blank :Non-IC Magnetic E :Non-IC Electronic	Blank :37W	Blank :120V -27 :277V	/LBL20 :20W Derating /LBL35 :35W Derating

Note: Wattage limitations on compatible items must be met.

ORDERING EXAMPLE : LSH1399