


## LSH99PR - SHALLOW REMODEL CFL HOUSING

### 4" COMPACT FLUORESCENT HOUSINGS



### SPECIFICATION

CFL 13W Max TTT

**Application:** General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

**Housing:** Pre-wired housing adjusts up to 1 1/4" ceiling thickness. This housing has torsion remodeling clips for secure installation. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out (above ceiling access is not required).

**Mounting:** Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

**Socket:** Thermo-plastic socket UL Listed rated for high temperature and provides nickel plated contacts. Accepts 4-Pin lamps with electronic ballast selection.

**Junction Box :** 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (7) 3/4" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

**Insulation Contact:** Non IC rated housing must be kept 3" from insulation. IC rated housing rated for direct contact with low to medium density loosefill blown and rolled insulation. For use with high density loose fill blown insulation, reduce rated lamp wattage accordingly (roughly %15-%20).

**Safety Labels:** ETL/CETL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

**Airflow:** Airtight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

**Emergency Option:** Emergency back-up operates one lamp for a minimum of 90 minutes at 750 Lumens in case of power outage. Unit is remotely mounted. It includes battery, charger, and test switch with indicator light. Consult Factory for 1300 Lumen Package.

**Label:** cETL Listed

### COMPATIBILITY

 <b>LR944</b> PHENOLIC BAFFLE NARROW APERTURE	 <b>LR925</b> ALBALITE	 <b>LR944</b> PHENOLIC BAFFLE NARROW APERTURE
 <b>LRS924</b> DECO GLASS DOME W/ REFLECTOR	 <b>LRS953</b> DECO GLASS-SHIELD (CONE)	 <b>LRS923</b> FRESNEL LENS W/ REFLECTOR
 <b>LRS922</b> DECO FROSTED GLASS W/ REFLECTOR	 <b>LRS912</b> PATTERNED GLASS W/ REFLECTOR	 <b>LRS924</b> DECO GLASS DOME W/ REFLECTOR
 <b>LRS925</b> FROSTED TRIMS W/ REFLECTOR	 <b>LRS935</b> EYELID WALL WASH W/ REFLECTOR	 <b>LR999</b> SHALLOW REFLECTOR
 <b>LRS912</b> PATTERNED GLASS W/ REFLECTOR	 <b>LRS922</b> DECO FROSTED GLASS W/ REFLECTOR	 <b>LRS923</b> FRESNEL LENS W/ REFLECTOR

Please see website for more compatible items.

### FEATURE:



ORDERING EXAMPLE : LSH99PRICAE

LSH99PR	WATTAGE	OPTIONS
LSH99PR	<b>E</b> :13W	<b>Blank</b> :120V
	<b>ICAE</b> :13W IC-Airtight	<b>-27</b> :120V/277V
		<b>-EM</b> :Emergency

\* 277V Not available for 13W magnetic.

ID# : 364