
TYPE

SL700: 11" OPEN FACE LED STEP LIGHT

(11W/20W)





























- High Quality Die-Cast Construction
- High 80 CRI
- 120V/277V Option
- 5-Year Warranty
- 32W CFL Equivalent

ORDERING: SL700B-L15UE-DUN-T30

SL700 Fixture Finish Options Lumens Color Temperature

Finish		Lumens		Options		Color Temperature	
Black	В	11W/1000lm	Blank	120V	Blank	3000K	-T30 ¹
White	W	20W/1500lm	-L15	120V/277V	UE	3500K	-T35 ²
Silver	N^1			120V/277V	UE-DUN	4000K	-T40
Bronze	BZ ¹			2-Wire, ELV & 0-10V Dimming		5000K	-T50 ²
				0-10v Diffilling		Color Changing	-RGBW



¹Extended Lead Time may apply. ²Special Order. Extended lead times may apply.

2023.09.18



SL700: 11" OPEN FACE LED STEP LIGHT (11W/20W)

SPECIFICATION

Recessed Wall Luminaire designed for commercial, architectural, and residential installation. Designed to conform to the architectural requirements for low mounting heights for the illumination of steps, stairways, walkways, aisles, ramps and other indoor and outdoor applications. Can be mounted vertically.
High grade die cast aluminum with an integral wiring compartment, silicone gasket. Two (2) 1/2-14 NPSM conduit provided.
Rectangular open with "side grill" one-piece high grade die cast aluminum faceplate with a high corrosion-resistant powder coat finish and semi-translucent polycarbonate opal lens. Faceplate is installed by four (4), captive, tamper resistant, stainless steel screws.
120V/277V Modular LED Engine (Field Replaceable) Consult Factory for dimming and sensor options.
UL / cUL / ETL / cETL Listed, suitable for wet location and for all types of constructions including use in poured concrete, Type IC (CF lamps), Type Non-IC (CF, T10 40W max. lamps), ADA compliant and suitable for installation within 4 feet of the ground Assembled in USA. (IP65).
Covered by a 5-Year Warranty to be free of defects in materials and craftsmanship.
Available in Black, White, Silver and Bronze.
Available in 11W/1000lm and 20W/1500lm.
Available in 3000K, 3500K, 4000K, 5000K and Color Changing.
1000 Lumens delivered
Color Rendering Index (CRI): 80
Lamp Equivalents: 100W A19 32W CFL.