


Remodel IC Airtight CFL Housing w/ Deco Glass Open Dome Baffle

LH276 SERIES - 6" COMPACT FLUORESCENT RECESSED LIGHTING



SPECIFICATION

Ceiling cut-out: 6 1/4"

Application: General purpose recessed downlight housing for medium to high ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the proper décor and illumination.

Housing: Pre-wired .042" steel housing adjusts up to 1 1/2" ceiling thickness. This housing has torsion remodeling clips for secure installation. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out (above ceiling access is not required).

Mounting: Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

Ballast: Electronic Class P 60Hz Ballast with Inherent thermal protection. For Double Twin Tube (DTT) or Triple Twin Tube Lamps (TTT). Sound A rated. Micro-Processor controlled. Min. starting temperature -10°C. Accessible from above or below the ceiling. Contact factory for detailed technical information on ballast specifications. Note: For dimming applications must use compatible dimmer switch. Consult specific ballast manufacturer for up-to-date compatibility list.

Socket: Thermo-plastic socket UL Listed rated for high temperature and provides nickel plated contacts. Accepts 4-Pin lamps with electronic ballast selection.

Insulation Contact: IC rated housing rated for direct contact with low to medium density loosefill blown and rolled insulation.

Airflow: Airtight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Emergency Option: Emergency back-up operates one lamp for a minimum of 90 minutes at 750 Lumens in case of power outage. Unit is remotely mounted. It includes battery, charger, and test switch with indicator light. Consult Factory for 1300 Lumen Package.

Label: UL Listed, cETL Listed

FEATURE:




Application: Decorative glass trims add a unique architectural dimension to your lighting design. These attractive glass trims that emit a warm and glowing illumination are available in various colors. Each glass trim and color combination will create an artful illumination that compliments any interior environment.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Label: UL Listed, cETL Listed

Limitation: Not for use w/Shallow Housings.



REMODEL IC AIRTIGHT CFL HOUSING

LH276RICA CFL 32W Max. DTT/TTT

WATTAGE	BALLAST	OPTION
LH276RICA-13:13W	UD :0-10V Dimming (120V/277V)	Blank :None
LH276RICA-18:18W	E :Electronic (120V)	-EM :Emergency
LH276RICA-26:26W	E-27:Electronic (120V/277V)	-FS :Fuse
LH276RICA-32:32W		
LH276RICA-42:42W		

DECO GLASS OPEN DOME BAFFLE

LR470 CFL 18W Max DTT, 32W TTT

BAFFLE FINISH	RING FINISH	GLASS
LR470W :White	Blank :White	-AM :Amber
LR470B :Black	B :Black	-BL :Blue
LR470N :All Natural*	N :Natural	-FR :Frosted
LR470CO :All Copper*	CO :Copper	
LR470MO :All Mocha*	MO :Mocha	

* Comes standard with a matching ring finish. Use "W" for White Ring.

Ordering example: LH276RICA-13E-27-EM/LR470W-AM

2016.8.29

File Located online www.liton.com/spec

ID #: 288_297