


## Remodel Shallow Housing w/ Wall Wash w/ Baffle

### LH7 SERIES - 6" LINE VOLTAGE RECESSED LIGHTING



#### SPECIFICATION

*Ceiling cut-out: 6 1/4"*

**Application:** General purpose recessed downlight housing for medium to high ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the proper décor and illumination.

**Housing:** Pre-wired housing adjusts up to 1 1/4" ceiling thickness. This housing has torsion remodeling clips for secure installation. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out (above ceiling access is not required).

**Mounting:** Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

**Socket:** Standard porcelain medium screw base socket with high temperature leads.

**Junction Box:** 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with 3/4", 1" and Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

**Insulation Contact:** Non IC rated housing must be kept 3" from insulation. IC rated housing rated for direct contact with low to medium density loosefill blown and rolled insulation. For use with high density loose fill blown insulation, reduce rated lamp wattage accordingly (roughly %15-%20).

**Safety Labels:** UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

**Label:** UL Listed, cETL Listed


#### FEATURE:



**Application:** This traditional style uses a stationary socket and a reflector to create a smooth illumination along the surface of the wall.

**Mounting:** Steel pressure springs mounted on trim to ensure positive retention inside housing.

**Label:** UL Listed, cETL Listed



#### REMODEL SHALLOW HOUSING

**LH27RICA** 120V 90W Max A19/PAR30/PAR38 MED E26

##### RATING

LH27RICA :IC Airtight

#### WALL WASH W/ BAFFLE

**LR45** 120V 100W Max PAR30/A19

##### BAFFLE FINISH

LR45W :White  
LR45B :Black  
LR45N :Natural  
LR45CO :Copper

##### RING FINISH

Blank :White

**Ordering example:** LH27RICA/LR45W