
Liton°

Remote Housing - No Transformer w/ MR11 Baffle

LH1299 SERIES - 2" LOW VOLTAGE RECESSED LIGHTING



H: 3 1/2" (37W), 4 1/2" (50W)



FEATURE:



SPECIFICATION

Ceiling cut-out: 2 3/4"

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired .05" baked enamel 1-piece drawn steel housing adjusts up to 1-1/4" ceiling thickness. Trim is secured with torsion wing springs.

Mounting: Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

Remote Transformer: For use with thermaly protected electronic low voltage transformer (not supplied) to be mounted in remote location away from fixture.

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box: 16 gauge pre-wired aluminum Junction Box, suitable for through branch wiring for a maximum of (4) #12 AWG wires. Furnished with (2) 3/4" knock-outs. Screw-in or out covers for easy access and ground wire. Equipped with safety standard fitting for flex-

Insulation Contact: Non-IC rated housing must be kept 3" from insulation.

Tel: 323.904.0200

Safety Labels: ETL/CETL listed. Suitable for damp locations. NYC approved: Calendar

Label: cETL Listed

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.


Lens Inclusion: Clear glass protective safety lens included in packaging

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Adjustability Lamp can be titled 35° degrees vertically.

Accessories: Takes (1) 1 3/8" Media.

Label: cETL Listed



REMOTE HOUSING - NO TRANSFORMER 12V Out 37W Max MR11/MR16 LHR1299

WATTAGE LHR1299 :37W LHR1299-50:50W **MR11 BAFFLE** 12V 35W Max MR11 LR1213

FINISH LR1213W : All White LR1213B :Black Baffle/White Ring LR1213N :All Natural Metal LR1213CO : All Copper

Ordering example: LHR1299/LR1213B

