


## Remote Housing - No Transformer w/ MR16 Reflector

### LH1299 SERIES - 2" LOW VOLTAGE RECESSED LIGHTING



#### SPECIFICATION

Ceiling cut-out: 2 3/4"

**Application:** General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

**Housing:** Pre-wired .05" baked enamel 1-piece drawn steel housing adjusts up to 1-1/4" ceiling thickness. Trim is secured with torsion wing springs.

**Mounting:** Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

**Remote Transformer:** For use with thermally protected electronic low voltage transformer (not supplied) to be mounted in remote location away from fixture.

**Socket:** 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

**Junction Box:** 16 gauge pre-wired aluminum Junction Box, suitable for through branch wiring for a maximum of (4) #12 AWG wires. Furnished with (2) 3/4" knock-outs. Screw-in or out covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

**Insulation Contact:** Non-IC rated housing must be kept 3" from insulation.

**Safety Labels:** ETL/CETL listed. Suitable for damp locations. NYC approved: Calendar #41937.

**Label:** cETL Listed

#### FEATURE:



**Application:** Perfect solution for low-profile design in hard-to-light spaces.


**Gasket:** Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.

**Lens Inclusion:** Clear glass protective safety lens included in packaging.

**Mounting:** Steel pressure springs mounted on trim to ensure positive retention inside housing.

**Accessories:** Takes up to (3) 2" Media.

**Label:** cETL Listed



#### REMOTE HOUSING - NO TRANSFORMER

##### LHR1299 12V Out 37W Max MR11/MR16

WATTAGE
LHR1299 :37W
LHR1299-50 :50W

#### MR16 REFLECTOR

##### LR1221 12V/120V 50W MR16

FINISH	RATING
LR1221W :All White	Blank :Damp Location
LR1221B :Black Reflector/ White Ring	-WL :Wet Location
LR1221C :Clear Reflector w/White Ring	
LR1221N :All Natural Metal	
LR1221CO :All Copper	
LR1221SN :Satin Reflector/Natural Ring	

Ordering example: LHR1299/LR1221B-WL