


Low Voltage Housing w/ Pinhole MINI-ARC PHANTOM TRIMLESS



SPECIFICATION

Ceiling cut-out: 5 7/8"

Application: Architectural-grade recessed "Trimless" downlight for low to medium height ceilings for residential commercial installations. Trimless design provides a clean unobstructed "zero-sight" line ceiling. Die-Cast aluminum plaster frame disc installed on housing for easy installation. A variety of trims compatible styles and finishes are available to achieve the proper décor and illumination.

Housing: Pre-wired housing with Die-Cast adjustment plate with pre-set ceiling thickness for easy installation in 1/2", 5/8", 3/4" and 1 inch ceilings. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with QuickLok mounting mechanism for an easy scratch free installation.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Transformer: Class 2 Noise-Free Electronic transformer installed adjacent to Junction Box, bottom and top accessible. Dimmable with dimmers designed for Electronic Low Voltage Loads. Thermally protected rated for 90° C.

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box: 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with 3/4", 1" and Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non IC rated housing must be kept 3" from insulation. IC rated housing rated for direct contact with low to medium density loosefill blown and rolled insulation. For use with high density loose fill blown insulation, reduce rated lamp wattage accordingly (roughly %15-%20).

Safety Labels: ETL/CETL listed. Suitable for damp locations. NYC approved: Calendar #41937.

Label: cETL Listed

Assembled in USA


FEATURE:



Applications: Mini-Arc 'Trimless' trims provide a flat, unobstructed 'zero-sight line' view of the ceiling. Trims easily install into a die-cast aluminum adjustment plate that mounts onto the housing. This miniature Pinhole trim is perfect for commercial and high-end residential applications. Its small aperture makes it ideal for strategic placement where tight beam spread control is required.

Accessories: Takes (1) 2" Media.

Label: UL Listed, cETL Listed



LOW VOLTAGE HOUSING LHX4LV

LIGHT SOURCE	
LHX4LV	:12V 50W Bi-Pin MR16
LHX4LV75	:12V 75W Bi-Pin MR16
LHX4LV75-27	:12V 75W Bi-Pin MR16 (277V, Electronic)
LHX4LVICA	:12V 50W Bi-Pin MR16 (Insulation Contact, Airtight)

PINHOLE LRX419

FINISH	RATING
LRX419W :White	Blank :Damp
	WL :Wet Location

Ordering example: LHX4LVICA/LRX419WWL