


Shallow Remodel Housing w/ Wall Wash Baffle

LH1499 SERIES - 4" LOW VOLTAGE RECESSED LIGHTING



SPECIFICATION

Ceiling cut-out: 4 1/4"

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired housing adjusts up to 1 1/4" ceiling thickness. This housing has torsion remodeling clips for secure installation. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out (above ceiling access is not required).

Mounting: Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

Transformer: Class 2 Noise-Free Electronic transformer installed adjacent to Junction Box, bottom and top accessible. Dimmable with dimmers designed for Electronic Low Voltage Loads. Thermally protected rated for 90° C.

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box: 16 gauge pre-wired aluminum Junction Box, suitable for through branch wiring for a maximum of (4) #12 AWG wires. Furnished with (2) 3/4" knock-outs. Screw-in or out covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non-IC rated housing must be kept 3" from insulation.

Safety Labels: ETL/CETL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: cETL Listed

FEATURE:



Application: Wall Wash trims provide excellent accent lighting and add contrast to any general lighting applications. The advantage of utilizing wall wash trims, is the ability to deliver the desired accent lighting to bring attention to the object and not the light source.


Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.

Lens Inclusion: Clear glass protective safety lens included in packaging.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Accessories: Takes (1) 2" Media.

Label: UL Listed, cETL Listed



SHALLOW REMODEL HOUSING

LSH1499R 12V Out 37W Max MR16

RATING	WATTAGE	VOLTAGE	OPTION
LSH1499RE :Electronic	Blank :37W	Blank :120V	Blank :None
		-27 :277V (Electronic*)	

* Available with 120V/277V Magnetic Option, consult factory.

WALL WASH BAFFLE

LR1495 12V/120V 50W MR16

BAFFLE FINISH	RING FINISH
LR1495W :White	Blank :White
LR1495B :Black	
LR1495N :Natural	
LR1495CO :Copper	

Ordering example: LSH1499RE/LR1495W