


Shallow CFL Housing w/ Shallow Reflector

LR99P SERIES - 4" COMPACT FLUORESCENT RECESSED LIGHTING



SPECIFICATION

Ceiling cut-out: 4 1/2"

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Socket: Thermo-plastic socket UL Listed rated for high temperature and provides nickel plated contacts. Accepts 4-Pin lamps with electronic ballast selection.

Insulation Contact: Non IC rated housing must be kept 3" from insulation. IC rated housing rated for direct contact with low to medium density loosefill blown and rolled insulation. For use with high density loose fill blown insulation, reduce rated lamp wattage accordingly (roughly %15-%20).

Airflow: Airtight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Safety Labels: ETL/CETL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

"Safety Labels: ETL/CETL listed for through- branch wiring (8) No.12 AWG 90°C and suitable for damp and wet locations (when use with appropriate trim designs). NYC approved: Calendar #41937."

Emergency Option: Emergency back-up operates one lamp for a minimum of 90 minutes at 750 Lumens in case of power outage. Unit is remotely mounted. It includes battery, charger, and test switch with indicator light. Consult Factory for 1300 Lumen Package.

Label: cETL Listed

FEATURE:




Application: Used for general lighting applications, The 4" reflector trim, with its clean and durable die-cast construction ring, provides a smooth illumination in short throw distances such as general spaces as well as tighter spaces such as soffits and counters.

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Label: UL Listed, cETL Listed



SHALLOW CFL HOUSING

LSH99P CFL 13W Max TTT

WATTAGE	OPTIONS
LSH99PE :13W (Electronic)	Blank :120V
LSH99PICA :13W IC-Airtight (Electronic)	-27 :120V/277V
	-EM :Emergency

* 277V Not available for 13W magnetic.

SHALLOW REFLECTOR

LR999 CFL 13W Max DTT, 26W TTT

REFLECTOR FINISH
LR999B :Black Reflector/ White Ring
LR999C :Clear Reflector/ White Ring
LR999N :All Natural
LR999CO :All Copper
LR999MO :All Mocha
LR999S :Satin Haze Reflector/ White Ring
LR999SN :Satin Reflector/ Natural Ring
LR999W :White Reflector/ White Ring

* Comes standard with a matching ring finish.

Ordering example: LSH99PE-EM/LR999B