


## WD1360-USA : 6" ROUND

1-DIRECTION WALL MOUNT (IP65) 1000LM - 2600LM (10W/15W/22W/30W)



### • Produced in USA

- Uniform, Low Glare Illumination
- Singular COB light source
- New Integral Emergency Option
- 13' Mtg. Ht., 22' O.C. Spacing (1000 lumen package)
- 25' Mtg. Ht., 22' O.C. Spacing (1500 lumen package)
- 5-Year Limited Warranty
- Photocell Available
- Available with Type IV/Forward Throw Optics
- IK08 Rated
- New Die-Cast Mounting Plate (-WPDC6)

### ORDERING : WD1360-USAB-L15-B20-UE-D10-EMAC-T27-LVR

#### WD1360-USA

Fixture	Finish	Lumen	Optics	Control	Emergency Options	LED	Options
<b>Finish</b>		<b>Optics</b>		<b>Control<sup>3</sup></b>		<b>LED</b>	
White (RAL 9003) <b>W</b>		<i>Standard Beams</i>		Non-Dimming (120V)	<b>Blank</b>	2700K (90 CRI)	<b>-T27</b>
Silver (RAL 7037) <b>S</b>		Wide Flood	<b>Blank</b>	0-10V Dimming (120V/277V)	<b>UE-D10</b>	3000K (90 CRI)	<b>-T30</b>
Bronze (RAL 8019) <b>BZ</b>		Narrow Spot	<b>-B10</b>	<b>Emergency Options</b>		3500K (90 CRI)	<b>-T35</b>
Black (RAL 9005) <b>B</b>		Spot	<b>-B20</b>	None	<b>Blank</b>	4000K (90 CRI)	<b>-T40</b>
Light Silver (RAL 7036) <b>LS<sup>1</sup></b>		Flood	<b>-B45</b>	Remote Emergency	<b>-EMAC</b>	5000K (80 CRI)	<b>-T50</b>
Dark Grey (RAL 7015) <b>DG<sup>1</sup></b>		<i>CleanBeam™ Option</i>		BackPack (Side Mount)	<b>-EMB-SD<sup>6</sup></b>	<b>Options</b>	
Metallic Gold (RAL 1001) <b>MG<sup>1</sup></b>		10° Pencil Beam	<b>-CB10</b>	BackPack (Face Mount)	<b>-EMB-FC<sup>6</sup></b>	None	<b>Blank</b>
Metallic Black (RAL 7021) <b>MB<sup>1</sup></b>		15° Clean Beam	<b>-CB15</b>	BackPack (Empty, Side Mount)	<b>-EMB-BLANK-SD<sup>5</sup></b>	Hex-Cell Louver	<b>-LVR<sup>10</sup></b>
<b>Lumen</b>		35° Clean Beam	<b>-CB35</b>	BackPack (Empty, Face Mount)	<b>-EMB-BLANK-FC<sup>5</sup></b>	Photocell Sensor	<b>-SDL</b>
1000lm (10W)	<b>Blank</b>	<i>Specialty Beams</i>				120V,277V	
1500lm (15W)	<b>-L15</b>	Wall Wash	<b>-BWW</b>			Integral Junction Box	<b>-JBL, JBR<sup>9</sup></b>
2200lm (22W)	<b>-L20</b>	Forward Throw (Type IV)	<b>-BIV</b>			1-Entry	
2600lm (30W)	<b>-L26</b>	Type II (110°x 40°)	<b>-BII<sup>2</sup></b>			Integral Junction Box	<b>-JB2</b>
						2-Entries	
						Junction Box, Conduit	<b>-JBT</b>
						Top Entry	
						Surge Protector	<b>-SRG</b>
						Cold Weather	<b>-CW<sup>4,6</sup></b>
						Glare Shield	<b>-SH</b>
						Marine Grade Finish	<b>-MGD<sup>1</sup></b>
						Die-Cast Oversized Mounting Plate	<b>-WPDC6</b>

<sup>1</sup> Special Order Finish. Minimum order quantity (MOQ) applies. Orders less than MOQ are subject to a special paint set-up fee for the quantity ordered. Extended lead times may apply. Consult Factory.

<sup>2</sup> Special Order. Minimum order quantity (MOQ), extended lead time may apply. Consult Factory.

<sup>3</sup> Standard driver minimum starting temperature is -10°C / 14°F.

<sup>4</sup> Cold Weather Start (-CW) Starting Temperature -30°C / -22°F.

<sup>5</sup> Blank EM enclosure available for non-EM units to provide a seamless design aesthetic when EM enabled products are installed.

<sup>6</sup> (-EMB-SD) and (-EMB-FC) are not compatible with (-CW) option.

<sup>9</sup> Must Specify Left or Right, see Page 7 for more details.

<sup>10</sup> (-LVR) Hex-Cell Louver is not compatible with CleanBeam Options (-CB10), (-CB15), (-CB35).

Energy Efficient Chip-On-Board (COB) Singular LED Light source provides for smooth uniform light output, eliminating the multiple shadow effect seen by multiple LED source products. Binned with 3-Step MacAdam Ellipses as recommended by Ansi Standard. Available in 2700K, 3000K, 3500K, 4000K, and 5000K.

Custom RAL Color: Please note that we appreciate custom finishes. Custom finishes are subject to a special paint setup fee for the quantity ordered. Extended lead times may apply. Consult Factory.

## SPECIFICATION

### Application


This WD1 series single direction wall mount luminaire can be used for both interior and outdoor locations. The single reflector design can be used for direct illumination downward or indirect illumination upward for new construction or retrofit installations. Typical locations are in residential, commercial, and architectural facades and retail spaces that contain walls and/or columns.

### Housing/Arm


Housing and Arm are constructed of one piece high grade aluminum extrusion (Alloy 6061 <.04% Cu). Faceplate (with tempered glass lens) and end caps are of a robust die cast aluminum alloy and seal the housing top and bottom. Faceplate has a silicone o-ring to seal the flush lens and threads into housing. An aluminum alloy mounting plate with a U-bracket installs onto an electrical junction box and secures into the arm with two (2) flat head countersunk Phillips head stainless steel screws.

### Mounting:

The standard mounting plate is a 6" high x 4-1/2" plate with a U-Bracket that installs directly onto 3-1/2" or 4" octagonal electrical junction box. (-WPDC6) is a die-cast oversized 6-3/4" high x 4-5/8" plate with a flat bracket designed to mount directly onto a 4" square junction box or a 3-1/2" or 4" octagonal electrical box.



### Finish:



A 7-stage electrostatic, polymer process provides an outdoor textured powder coat finish that delivers outstanding durability, superior anti-aging, resistance to corrosion and UV-degradation. Consult factory for Custom Color. (More Information)

#### Standard Finishes:

White: RAL 9003 (W)  
 Silver: RAL 7037 (S)  
 Bronze: RAL 8019 (BZ)  
 Black: RAL 9005 (B)

#### Special Order Finishes:

Light Silver: RAL 7036 (LS)  
 Dark Gray: RAL 7015 (DG)  
 Metallic Gold: RAL 1001 (MG)  
 Metallic Black: RAL 7021 (MB)

## SPECIFICATION (Continued)

### Certifications and Listings:



ETL / cETL Listed to UL1598 and UL8750 standards.

Suitable wet locations. (IP65)

Assembled in USA.

IK08 rated for impact resistance.

### Caution:

LITON recommends use of surge protectors on the power entering LED Housings.  
Surge damage is not covered by warranty.

### Warranty

Covered by a 5-Year Warranty to be free of defects in materials and craftsmanship. Fixture should not be installed in applications with ambient temperature above 50°C/122°F. Doing so will result in reduced lamp life and voided warranty.

### Optics

Multifaceted aluminum reflector produces low glare illumination with multiple light control options.

### Standard Beam:

Used for maximum light output and visible field angle.

### CleanBeam™:

Used for a direct uniform light output with minimized field angle and to enhance building aesthetics.

### LED

COB (Chip on Board) singular LED light source provides for smooth, uniform light output, eliminating the imaging produced by multiple LED source optics.

### Lumen Maintenance:


Lumen Maintenance is minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

### Lumen Options (Nominal):

1000lm (10W)  
1500lm (15W)  
2200lm (22W)  
2600lm (30W)

### Color Temperature:

Binned with 4-step MacAdam ellipses as per ANSI Standard recommendation.



COLOR TEMP: 2700K 3000K 3500K 4000K 5000K  
CRI: 90 90 90 90 80

## SPECIFICATION (Continued)


### REMOTE LOCATION EMERGENCY INVERTER (-EMAC): 25W and 40W

For installation away from the surface of the building in remote hidden location.

- Hidden Emergency Equipment
- Must be installed in Dry Locations
- Wattage package will determine if 25W or 40W battery gets sent; corresponding wiring diagrams below
- 170 VDC output to AC DRIVER during EM mode


**Not rated for outdoor mounting. Damp location rated.**

#### <25W LOAD



Input Voltage:	120-277VAC/60Hz
Output Voltage:	170VDC (120VAC Equivalent)
Wattage:	25W
Switching Time:	<1s
Charging Time:	24h
Operating Time:	90 minutes
Minimum Temperature:	0°C
Maximum Temperature:	50°C
Maximum Lumens:	2200lm
Self-Diagnostic:	No


#### <40W LOAD



Input Voltage:	120-277VAC/60Hz
Output Voltage:	170VDC (120VAC Equivalent)
Wattage:	40W
Switching Time:	<1s
Charging Time:	24h
Operating Time:	90 minutes
Minimum Temperature:	0°C
Maximum Temperature:	50°C
Maximum Lumens:	3500lm
Self-Diagnostic:	Yes

#### >40W LOAD

- 0-10V dimmable driver required




## SPECIFICATION (Continued)


### BackPack Side Mount (-EMB-SD/FC):

Eliminates need for long runs back to remote emergency battery location. Installs directly on building surface. Ideal for locations wanting same mounting aesthetics for Emergency and Non-Emergency fixtures without the use of remote Emergency power. Can be fed from recessed wall mounted junction box from the back of fixture or surface conduit from side of fixture.

- Wet location rated.
- 120V-347V operation.
- Self diagnostic.
- Integral surge protector for emergency driver only.
- Includes (2) 1/2" NPT knock-outs.
- Optional -EMB-BLANK can be used to maintain a common aesthetic when -EMB-FC are used.




Shown with EMB-FC Option




Shown with EMB-SD Option

Output Power:	18 Watts (Max)
Input Power:	7 Watts (Max)
Emergency Operation:	≥90 minutes
Operating temp:	0°C/32°F to 50°C/122°F
Input Voltage:	120V-347 VAC
Battery:	Recyclable lithium battery 24 Hour Recharge 7-10 Year Life Expectancy
Charge Time:	24 hours
Max Distance:	25'
Weight:	3-3/4 lbs.
Warranty:	5-year
Surge Protection:	Integral 3,000V
Self-diagnostic testing:	Monthly 30 sec. test, Yearly 90 min. test to verify proper emergency operation per life safety code requirements.

### (<18W)



### (18W-200W)




**SPECIFICATION (Continued)**

**Additional Options**

---

Optional J-Box (Direct Conduit Entry):

For use with mounting locations without a recessed junction box.  
 Allows for direct mounting to building surface. Arm may be configured for up to 3 conduit entries (1/2") total; 2 on the sides, 1 on top. .



Configure as:

- JBL, -JBR: (1) conduit entry from left or right looking at fixture
- JB2 (2) conduit entry on sides
- JBT (1) conduit entry on top

Hexcell Louver (-LVR):

3 mm /.125" (size of the cells) - matte black finish, 45° glare cutoff, unframed.



Photocell (/SDL):


Sensor enables automatic on/off operation based on ambient light levels, providing dusk-to-dawn functionality.



- Voltage: 120V, 277V
- Power Consumption .5W
- On/Off Levels: On @ 0-2fc / Off @ 2fc or more
- Warranty: 2-Year / 5,000 Cycles
- Sensor Size: 3/8"
- Rating: UL/cUL

Surge Suppressor (/SRG):

Protects driver against surges in line voltage/current (20KV, 1.2/50µS & 10KA, 8/20µS).



Provides a positive indication of end-of-life by opening voltage to the load.  
 Surge suppressor is a perishable device requiring periodic replacement.  
 Not a warranted item.



## SPECIFICATION (Continued)

### Electrical

---

LED Driver: AC 50/60Hz Electronic Direct Current Class 2 driver integrally mounted.  
Power Factor > 0.90. See Dimming Section for voltage and wiring.

Minimum Operating Temperature:

Standard: -10°C/14°F


Cold Weather Option: (-CW) -30°C/-22°F

### Control Options

---

#### 0-10V Driver 120V/277V (UE-D10):

Compatible with most existing 0-10V systems. Also known as fluorescent or 5-Wire dimming. Allows smooth dimming down to 5% depending upon the dimmer's limitations. Compatible with daylight harvesting controls.



### Marine Grade

---

The fixture features a marine-grade textured powder coat finish engineered to withstand extreme environmental conditions, including prolonged exposure to UV radiation, salt air, and moisture, which are prevalent in coastal and high-humidity environments.

A multi-stage surface preparation, finishing, and curing process ensures maximum adhesion, durability, and corrosion resistance. The coating system undergoes rigorous salt spray (ASTM B117) testing, overbake resistance verification, and pencil hardness testing to validate its robustness against degradation.


The marine-grade powder coat is applied as a 30–50 µm bottom layer, providing a strong anti-corrosion foundation. This is further enhanced by a surface coat using a standard architectural-grade powder application with a total thickness of 80–120 µm, ensuring superior resistance to wear, impact, and environmental stressors.

## PHOTOMETRY – WD1360B (L26)


### Footcandles On Wall

5.0 fc 2.0 fc 1.0 fc .5 fc


**STANDARD BEAM – Wide Flood (Blank)**  
3 ft Grid




**CLEANBEAM™ – (-B02)**  
3 ft Grid




**CLEANBEAM™ – (-CB20)**  
3 ft Grid



**CLEANBEAM™ – (-CB35)**  
3 ft Grid




**SPECIALTY BEAM – Wall Wash (-BWW)**  
3 ft Grid




### Footcandles On Wall and Ground

5.0 fc 2.0 fc 1.0 fc .5 fc


**STANDARD BEAM – Wide Flood (Blank)**  
3 ft Grid



**SPECIALTY BEAM – Type II (-BII)**  
3 ft Grid



**SPECIALTY BEAM – Type IV (-BIV)**  
3 ft Grid




2023.07.17

PHOTOMETRY – WD1360B (L26) (Cont.)


Footcandles On Ground (2 - Fixture Overlap)

5.0 fc 2.0 fc 1.0 fc .5 fc


**STANDARD BEAM – WIDE FLOOD (Blank) 8' Mounting**




**STANDARD BEAM – WIDE FLOOD (Blank) 16' Mounting**




**SPECIALTY BEAM – TYPE IV (-BIV) 8' Mounting**




**SPECIALTY BEAM – TYPE IV (-BIV) 16' Mounting**



**SPECIALTY BEAM – TYPE II (-BII) 8' Mounting**



**SPECIALTY BEAM TYPE II (-BII) 16' Mounting**



## LUMEN OUTPUT / LPW /BUG RATING

LM	W	Beam Spread	-T27 (2700K, 90 CRI)						-T30 (3000K, 90 CRI)						-T35 (3500K, 90 CRI)						Blank (4000K, 90 CRI)						-T50 (5000K, 80 CRI)					
			LM	LPW	cd	B	U	G	LM	L/W	cd	B	U	G	LM	LPW	cd	B	U	G	LM	LPW	cd	B	U	G	LM	LPW	cd	B	U	G
1000 lm	14.3	Wide FL	958	67	678	1	0	0	997	70	906	1	0	0	1011	71	716	1	0	0	1013	71	717	1	0	0	1207	84	855	1	0	0
		-B02	224	16	423	1	0	0	233	16	440	1	0	0	236	17	447	1	0	0	237	17	447	1	0	0	282	20	533	1	0	0
		-CB20	265	19	482	1	0	0	276	19	502	1	0	0	280	20	509	1	0	0	281	20	510	1	0	0	334	23	607	1	0	0
		-CB35	403	28	509	1	0	0	420	29	530	1	0	0	425	30	538	1	0	0	426	30	539	1	0	0	508	36	642	1	0	0
		-B10	1134	79	5609	2	0	0	1180	83	5840	2	0	0	1197	84	5921	2	0	0	1199	84	5933	2	0	0	1429	100	7070	2	0	0
		-B20	977	68	4490	2	0	0	1017	71	6633	2	0	0	1031	72	4740	2	0	0	1033	72	4749	2	0	0	1231	86	5659	2	0	0
		-B45	968	68	1891	2	0	0	1008	70	2448	2	0	0	1022	71	1997	2	0	0	1024	72	2001	2	0	0	1220	85	2384	2	0	0
		-BII	951	67	754	1	0	0	990	69	785	1	0	0	1004	70	796	1	0	0	1006	70	798	1	0	0	1199	84	951	1	0	0
		-BWW	906	63	613	1	0	0	943	66	638	1	0	0	956	67	647	1	0	0	958	67	648	1	0	0	1142	80	772	1	0	0
-BIV	906	63	613	1	0	0	943	66	638	1	0	0	956	67	647	1	0	0	958	67	648	1	0	0	1142	80	772	1	0	0		
-L15 (1500 lm)	13.9	Wide FL	1281	90	907	1	0	0	1334	96	709	1	0	0	1352	97	957	1	0	0	1355	97	959	1	0	0	1615	116	1143	1	0	0
		-B02	283	20	619	1	0	0	294	21	644	1	0	0	299	21	653	1	0	0	299	22	654	1	0	0	356	26	780	1	0	0
		-CB20	336	23	610	1	0	0	350	25	635	1	0	0	355	26	644	1	0	0	355	26	645	1	0	0	423	30	769	1	0	0
		-CB35	509	36	643	1	0	0	530	38	670	1	0	0	537	39	679	1	0	0	538	39	680	1	0	0	641	46	811	1	0	0
		-B10	1264	88	6257	2	0	0	1316	95	6514	2	0	0	1335	96	6605	2	0	0	1337	96	6618	2	0	0	1594	115	7886	2	0	0
		-B20	1316	92	6050	2	0	0	1370	99	4534	2	0	0	1389	100	6387	2	0	0	1392	100	6399	2	0	0	1659	119	7626	2	0	0
		-B45	1303	91	2545	2	0	0	1356	98	1990	2	0	0	1375	99	2687	2	0	0	1378	99	2692	2	0	0	1642	118	3208	2	0	0
		-BII	1241	87	984	1	0	0	1292	93	1025	1	0	0	1310	94	1039	1	0	0	1313	94	814	1	0	0	1564	113	1240	1	0	0
		-BWW	1137	80	769	1	0	0	1184	85	801	1	0	0	1201	86	812	1	0	0	1203	87	814	1	0	0	1431	103	968	1	0	0
-BIV	1137	80	769	1	0	0	1184	85	801	1	0	0	1201	86	812	1	0	0	1203	87	814	1	0	0	1433	103	970	1	0	0		
-L20 (2000 lm)	19.5	Wide FL	1745	122	1236	1	0	0	1817	93	830	1	0	0	1843	94	1304	1	0	0	1846	95	1307	1	0	0	2200	113	1557	1	0	0
		-B02	463	32	954	1	0	0	482	25	993	1	0	0	489	25	1007	1	0	0	490	25	1009	1	0	0	584	30	1202	1	0	0
		-CB20	549	38	997	1	0	0	571	29	1038	1	0	0	579	30	1052	1	0	0	581	30	1054	1	0	0	692	35	1257	1	0	0
		-CB35	834	58	1055	1	0	0	869	45	1098	1	0	0	881	45	1113	1	0	0	882	45	1116	1	0	0	1052	54	1329	1	0	0
		-B10	2022	141	9994	2	0	0	2106	108	10405	2	0	0	2135	109	10551	2	0	0	2139	110	10571	2	0	0	2549	131	12597	2	0	0
		-B20	1759	123	7728	2	0	0	1831	94	5913	2	0	0	1857	95	8158	2	0	0	1860	95	8173	2	0	0	2217	114	9740	2	0	0
		-B45	1776	124	3469	2	0	0	1849	95	2775	2	0	0	1874	96	3662	2	0	0	1878	96	3669	2	0	0	2238	115	4372	2	0	0
		-BII	1998	140	1584	1	0	0	2080	107	1649	1	0	0	2109	108	1672	1	0	0	2113	108	1676	1	0	0	2518	129	1997	1	0	0
		-BWW	1870	131	1265	1	0	0	1946	100	1317	1	0	0	1974	101	1335	1	0	0	1977	101	1338	1	0	0	2356	121	1594	1	0	0
-BIV	1870	131	1265	1	0	0	1946	100	1317	1	0	0	1974	101	1335	1	0	0	1977	101	1338	1	0	0	2356	121	1594	1	0	0		
-L26 (2600 lm)	29.3	Wide FL	2246	157	1590	1	0	0	2339	80	1114	1	0	0	2372	81	1679	1	0	0	2376	81	1682	1	0	0	2832	97	2005	1	0	0
		-B02	601	42	1249	1	0	0	626	21	1301	1	0	0	634	22	1319	1	0	0	636	22	1321	1	0	0	757	26	1575	1	0	0
		-CB20	712	50	1294	1	0	0	742	25	1347	1	0	0	752	26	1366	1	0	0	754	26	1368	1	0	0	898	31	1631	1	0	0
		-CB35	1082	76	1368	1	0	0	1126	38	1424	1	0	0	1142	39	1444	1	0	0	1144	39	1447	1	0	0	1364	47	1724	1	0	0
		-B10	2494	174	12307	2	0	0	2597	89	12812	2	0	0	2633	90	12992	2	0	0	2638	90	13016	2	0	0	3144	107	15512	2	0	0
		-B20	2306	161	10153	2	0	0	2401	82	7653	2	0	0	2434	83	10718	2	0	0	2439	83	10738	2	0	0	2907	99	12797	2	0	0
		-B45	2315	162	4522	2	0	0	2410	82	3725	2	0	0	2443	83	4773	2	0	0	2448	84	4782	2	0	0	2917	100	5699	2	0	0
		-BII	2567	179	2035	1	0	0	2672	91	2119	1	0	0	2710	92	2149	1	0	0	2715	93	2153	1	0	0	3235	110	2566	1	0	0
		-BWW	2404	168	1626	1	0	0	2502	85	1693	1	0	0	2537	87	1716	1	0	0	2542	87	1720	1	0	0	3024	103	2046	1	0	0
-BIV	2404	168	1626	1	0	0	2502	85	1693	1	0	0	2537	87	1716	1	0	0	2542	87	1720	1	0	0	3030	103	2049	1	0	0		