




## DL34JR2: 4" ROUND VANDAL RESISTANT RECESSED ADJUSTABLE DOWNLIGHT (IP65/IP67) 700LM (10W)



Shown with **Junction Box Option (-JB)**

Supplied with 36" Long Power Cord, Other Lengths Available, Consult Factory

Ceiling Cut-Out: 4-3/8"  
 Ceiling Thickness: 1-1/4" Max with thumb screws  
 1-1/2" Max without thumb screws



- Remote Emergency Available
- IP65 Standard, IP67 Rated Option
- Tamper Resistant Fasteners
- IK08 option available with Polycarbonate Lens
- Multiple Wireless Control Options
- Integral J-Box Option
- Anti-Ligature

### ORDERING : DL34JR2W-B45-T27

[Click for Full Specification Details](#)

Finish	Beam Spread	Control	Color Temperature	Emergency Options	Options
<b>Finish</b>		<b>Control</b>		<b>Color Temperature</b>	<b>Options</b>
White	<b>DL34JR2W</b>	Non-Dimming (120V)	<b>Blank</b>	2700K (80 CRI)	<b>-T27</b>
Silver	<b>DL34JR2S<sup>2</sup></b>	UniDim™ (120V/277V)	<b>UE-DUN</b>	3000K (80 CRI)	<b>-T30</b>
Basic Bronze	<b>DL34JR2BZ<sup>2</sup></b>	0-10V (120V/277V)	<b>UE-D10</b>	3500K (80 CRI)	<b>-T35</b>
Black	<b>DL34JR2B</b>	ELV and Triac (120V)	<b>-DIN</b>	4000K (80 CRI)	<b>-T40</b>
Light Silver	<b>DL34JR2LS<sup>2</sup></b>	0-10V 1% (120V/277V)	<b>UE-D10P1</b>		
Dark Grey	<b>DL34JR2DG<sup>2</sup></b>	UniSense - Integral Motion/ Photosensor (120V)	<b>SUN-INT<sup>1,4</sup></b>	<b>Emergency Options</b>	
Metallic Gold	<b>DL34JR2MG<sup>2</sup></b>	UniSense - Integral Motion/ Photosensor (120V/277V)	<b>SUN-INT-1227<sup>1,4</sup></b>	None	<b>Blank</b>
Metallic Black	<b>DL34JR2MB<sup>2</sup></b>	Casambi Wireless Dimming (120V/277V)	<b>-DCSM<sup>1</sup></b>	Remote Location	<b>-EMAC<sup>5</sup></b>
		BubblyNet Wireless System (120V/277V)	<b>-DBNT<sup>1</sup></b>	Emergency Inverter	
		SimplySnap Wireless System (120V/277V)	<b>-DSYN<sup>1,4</sup></b>		
<b>Beam Spread</b>					
Flood	<b>-B45</b>				
Wide Flood	<b>-B60</b>				

<sup>1</sup> Special order. Minimum Order, Extended lead time may apply. Consult Factory.  
<sup>2</sup> Special Order Finish. Minimum order quantity (MOQ) applies. Orders less than MOQ are subject to a special paint set-up fee for the quantity ordered. Extended lead times may apply. Consult Factory.  
<sup>3</sup> Starting temperature for -CW option -40°C/-40°F; see pg. 7.  
<sup>4</sup> Must be ordered with (-JB).  
<sup>5</sup> (-EMAC) is not compatible with (-CW) option.

Custom RAL Color: Please note that we appreciate custom finishes. Custom finishes are subject to a special paint setup fee for the quantity ordered. Extended lead times may apply. Consult Factory.