TYPE PROJECT

CATALOG#

DL36R2 : 6" ROUND VANDAL RESISTANT RECESSED DOWNLIGHT (IP65/IP67)

1000LM-2600LM (10W-30W)



Shown with **Junction Box** Option (-JB)

Ceiling Cut-Out: 6-1/2"
Ceiling Thickness: 1-1/4" Max with thumb screws
1-1/2" Max without thumb screws



Supplied with 36" Long Power Cord, Other Lengths Available, Consult Factory



Intertek 120V 277V 347V

U.S. Assembled Outdoor Wet Damp Location

Vandal Resistant Emergency Backup Cold Weather IC Rated

Marine Grade Downlight

- Remote Emergency Available
- IP65 Standard, IP67 Rated Option
- Tamper Resistant Fasteners
- IK08 option available with Polycarbonate Lens
- Multiple Wireless Control Options
- Integral J-Box Option
- Anti-Ligature

ORDERING : DL36R2W-L15-B10-T27

Click for Full Specification Details

Finish | Lumens | Beam Spread | Control | Color Temperature | Emergency Options | Options

Finish

White	**DL36R2W**
Silver	**DL36R2S**[2]
Bronze	**DL36R2BZ**[2]
Black	**DL36R2B**
Light Silver	**DL36R2LS**[2]
Dark Grey	**DL36R2DG**[2]
Metallic Gold	**DL36R2MG**[2]
Metallic Black	**DL36R2MB**[2]

Lumens

1000lm (10W)	**Blank**
1500lm (15W)	**-L15**
2200lm (22W)	**-L20**
2600lm (30W)	**-L26**

Beam Spread

Wide Flood	**Blank**
Narrow Spot	**-B10**
Spot	**-B20**
Flood	**-B45**
Wall Wash Optics	**-BWW**
Asymmetric (30° x 60°)	**-B3060**[1]

Control

Non-Dimming (120V)	**Blank**
UniDim (120V/277V)	**UE-DUN**
0-10V (120V/277V)	**UE-D10**
Incandescent (120V)	**-DIN**
0-10V 1% (120V/277V)	**UE-D10P1**
0-10V (347V)	**347-D10**[5]
UniSense - Integral Motion/ Photosensor (120V)	**SUN-INT**[1,6]
UniSense - Integral Motion/ Photosensor (120V/277V)	**SUN-INT-1227**[1,6]
Casambi Wireless Dimming (120V/277V)	**-DCSM**[1]
BubblyNet Wireless System (120V/277V)	**-DBNT**[1]
SimplySnap Wireless System (120V/277V)	**-DSYN**[1,6]

Color Temperature

4000K (90 CRI)	**Blank**
2700K (90 CRI)	**-T27**
2700K (97CRI)	**-T27-C97**
3000K (90 CRI)	**-T30**
3000K (97CRI)	**-T30-C97**
3500K (90 CRI)	**-T35**
5000K (80 CRI)	**-T50**
RGB+W Control (24VDC)	**-RGBWV24**[4]
590nm Amber (Turtle Safe)	**-TAM-LVR**

Emergency Options

None	**Blank**
Remote Location Emergency Inverter	**-EMAC**[7]

Options

None	**Blank**
Hex-Cell Louver	**-LVR**
Frosted Lens	**-FR**
Cold Weather	**-CW**[3]
Marine Grade Finish	**-MGD**[2]
IK08 Impact Rated Polycarbonate Lens	**-IK08**[1]
Integral Junction Box	**-JB**
Surge Protector	**-SRG**
72" Long Power Cord	**-CRD72**
IP67 Rated	**-IP67**[1]

[1] Special order. Minimum Order, Extended lead time may apply. Consult Factory.
[2] Special Order Finish. Minimum order quantity (MOQ) applies. Orders less than MOQ are subject to a special paint set-up fee for the quantity ordered. Extended lead times may apply. Consult Factory.
[3] Starting temperature for -CW option -40°C/-40°F; see pg. 7.
[4] Remote Power Supplies and Control Gear Required, Available with Wireless Bluetooth or DMX Control. See pg. 4 or consult factory for details.
[5] Not compatible with 1000lm selection; use with 1500lm and above.
[6] Must be ordered with (-JB).
[7] (-EMAC) is not compatible with (-CW) option.

Custom RAL Color: Please note that we appreciate custom finishes. Custom finishes are subject to a special paint setup fee for the quantity ordered. Extended lead times may apply. Consult Factory.