

# DLCT : CATENARY

CATENARY MOUNT (IP65) 1000LM - 2600LM (10W - 30W)



- Energy efficient, low glare LED Chip-On-Board light engine
- Beam spreads include NS, SP, FL, WFL and 2° Pencil Beam
- Wall Wash Optics available
- Emergency back up available
- Integral power supply
- 5-Year Limited Warranty

## ORDERING : DLCT360B-L15-B20UE-D10-EMB-T27-LVR-DM



[Click for Full Specification Details](#)

DLCT		Fixture	Fixture Finish	Lumen	Optics	Control	Emergency Options	LED	Options	Mount
<b>Fixture</b>		<b>Lumen</b>		<b>Control</b>		<b>LED</b>				
4" Round	<b>DLCT340</b>	1000lm (10W)	<b>Blank</b>	Non-Dimming (120V)	<b>Blank</b>	4000K (90 CRI)	<b>-T40</b>			
4" Square	<b>DLCTQ340</b>	1500lm (15W)	<b>-L15</b>	ELV and Triac Dimming (120V)	<b>-DIN</b>	2700K (90 CRI)	<b>-T27</b>			
6" Round	<b>DLCT360</b>	2200lm (22W)	<b>-L20<sup>1</sup></b>	0-10V Dimming (120V/277V)	<b>UE-D10</b>	2700K (97 CRI)	<b>-T27-C97<sup>2</sup></b>			
		2600lm (30W)	<b>-L26<sup>1</sup></b>	UniDim™ 0-10V, ELV, Triac Dimming (120V/277V)	<b>UE-DUN<sup>3</sup></b>	3000K (90 CRI)	<b>-T30</b>			
<b>Fixture Finish</b>		<b>Optics</b>		<b>Control</b>		<b>LED</b>				
White	(RAL 9003) <b>W</b>	<i>Standard Beams</i>		0-10V 1% Dimming (120V/277V)	<b>UE-D10P1</b>	3500K (90 CRI)	<b>-T35</b>			
Black	(RAL 9005) <b>B</b>	Wide Flood	<b>Blank</b>	347V 0-10V Dimming (347V)	<b>-347-D10<sup>1,7</sup></b>	5000K (80 CRI)	<b>-T50</b>			
Bronze	(RAL 8019) <b>BZ</b>	Narrow Spot	<b>-B10</b>	Casambi Wireless Dimming (120V/277V)	<b>-DCSM<sup>8</sup></b>	Amber - Limited Wavelength - 590nm (Turtle Safe with Louver)	<b>-TAM-LVR<sup>10</sup></b>			
Silver	(RAL 7037) <b>S</b>	Spot	<b>-B20</b>	BubblyNet Wireless System (120V/277V)	<b>-DBNT<sup>8</sup></b>	RGB+W Control (24VDC)	<b>-RGBWV<sup>24</sup></b>			
Light Silver	(RAL 7036) <b>LS<sup>2</sup></b>	Flood	<b>-B45</b>	SimplySnap Wireless System (120V/277V)	<b>-DSYN<sup>9</sup></b>	<b>Options</b>				
Dark Gray	(RAL 7015) <b>DG<sup>2</sup></b>	<i>Specialty Beams</i>		<b>Emergency Options</b>						
Metallic Gold	(RAL 1001) <b>MG<sup>2</sup></b>	Asymmetric (30° x 60°)	<b>-B3060</b>	None	<b>Blank</b>	None	<b>Blank</b>			
Metallic Black	(RAL 7021) <b>MB<sup>2</sup></b>	Variable Beam (20° - 50°)	<b>-BVR</b>	Wall Mount	<b>-EMB<sup>6</sup></b>	Frosted Lens	<b>-FR</b>			
				Emergency System		Hex-Cell Louver	<b>-LVR<sup>2</sup></b>			
						Cold Weather	<b>-CW<sup>1,3</sup></b>			
						Glare Shield	<b>-SH</b>			
						Cable Cross Brace	<b>-CXB</b>			
						Marine Grade Finish	<b>-MGD<sup>2</sup></b>			
						<b>Mount</b>				
						Direct Mount	<b>-DM<sup>5</sup></b>			
						Adjustable	<b>-ADJ<sup>5</sup></b>			
						Pendant	<b>-PD<sup>5</sup></b>			
						Stem 6"	<b>-STM06<sup>5</sup></b>			
						Stem 12"	<b>-STM12<sup>5</sup></b>			
						Stem 18"	<b>-STM18<sup>5</sup></b>			
						Stem 24"	<b>-STM24<sup>5</sup></b>			
						Stem 36"	<b>-STM36<sup>5</sup></b>			

<sup>1</sup> For DLCT360 only.  
<sup>2</sup> Special Order. Minimum order, extended lead time may apply. Consult factory. (Finish options 50 piece minimum. 10-12 week lead time)  
<sup>3</sup> Starting temperature -30°C/-22°F; see p. 7.  
<sup>4</sup> Available with wireless bluetooth or DMX control. Consult factory for details. Remote power supplies and control gear may be required.  
<sup>5</sup> Standard color is black unless the fixture is ordered white, in which case it will be white.  
<sup>6</sup> Basic bronze (BZ) standard finish. Black (B), and Silver (S) finish available. Contact factory for pricing  
<sup>7</sup> Not compatible with 1000lm. 347V Input with 0-10V Dimming available only with 1500lm and above. Consult factory for lead times.  
<sup>8</sup> Special Order.  
<sup>9</sup> Special Order. Sent with surface mount JBOX to allow for direct-conduit entry.  
<sup>10</sup> (-TAM-LVR) option only available with 1000lm (10W).

Custom RAL Color: Please note that we appreciate custom finishes. Custom finishes are subject to a special paint setup fee for the quantity ordered. Extended lead times may apply. Consult Factory.

## COMPATABILITY

### SUN-RMT

Remote Unisense™

