TYPE PROJECT

CATALOG#

LHAJLD4 : 4" LUMENBLAST

ADJUSTABLE ACCENT & LENSED WALL WASH, ROUND (1500LM - 5000LM)





Ceiling Cut-out: 4-3/4" Dia.
*Maximum angle, Adjustable Accent only.

Quickship | Damp Location | Emergency Backup | US Assembled

Sloped Ceiling | Dedicated LED | Adjustable | Downlight

Wall Wash | 120V | 277V | Intertek

347V | Motion/Daylight Sensor

- Illuminate up to 70' ceilings
- Adjustable to 35° angle and 355° of rotation
- Wall Wash to provide uniform, even illumination
- Highly efficient COB (Chip on Board) LED

ORDERING : LHAJLD420C050UE-DUN-B45-T30-FS/LRA471S

Click for Full Specification Details

LHAJLD4 /

Fixture | Lumens | Control | Beam Spread | Color Temperature | Frame Options | Trim

Fixture

Adjustable Downlight	**LHAJLD4**

Lumens (Nominal Delivered)

1500lm (9W)	**12C025**
2000lm (11W)	**15C035**
2500lm (19W)	**20C050**
3000lm (28W)	**25C070**
3500lm (39W)	**30C085**
4500lm (44W)	**35C105**
5000lm (60W)	**50C140**

Control[1]

Non-Dimming	**Blank**
Remote Driver	**-RMT**
TRIAC/ELV Dimming (120V)	**-DIN**
0-10V Dimming (120V/277V)	**UE-D10**
UniDim™ 0-10V, TRIAC/ELV Dimming (120V/277V)	**UE-DUN**
10%, Wireless Enocean Adapter (120V/277V)	**UE-DEN**
DMX Dimming with input via XLR5 (120V/277V)	**UE-DMXLR5**
DMX Dimming with input via RJ45 (120V/277V)	**UE-DMXRJ45**
1%, 0-10V Dimming	**UE-D10P1**
0-10V Dimming (347V)	**-347-D10**
Lutron Hi-Lume (120V/277V)	**UE-DHL**
1%, 2-Wire Incandescent (120V)	**DINP1**
Athena Wireless Node (120V)	**-AWN**
UniSense - Remotely Mounted Motion/Photosensor (120V)	**-SUN-RMT[6]**
UniSense - Remotely Mounted Motion/Photosensor	**-SUN-RMT-1227[6]**
Casambi Wireless Dimming	**-DCSM[5]**
BubblyNet Wireless System	**-DBNT[5]**
Lutron Vive Wireless Dimming Module	**-VIVE[5]**

Beam Spread

15° Narrow Spot	**-B15**
25° Narrow Flood	**-B25**
45° Flood	**-B45**
60° Wide Flood	**-B60**

Color Temperature

2700K, 80 CRI	**-T27**
2700K, 90 CRI	**-T27-C90**
3000K, 80 CRI	**-T30**
3000K, 90CRI	**-T30-C90**
3500K, 80 CRI	**-T35**
4000K, 80 CRI	**-T40**
Warm dimming 1850K-3000K	**-TWD[2]**
Tunable White 2700K-6500K	**-TTW[3]**

FRAME OPTIONS

None	**Blank**
Generator Transfer Device	**-GTD**
Single Fuse	**-FS**
10W Emergency Battery	**-EM**
Full Power Emergency Inverter	**-EMAC[4]**
Full Power Emergency Inverter (347V)	**-EMAC347[4]**
C-Channel Hanger Bar Set	**C260**
Adjustable C-Channel Hanger Bar Set	**C260-J**

Trim (Open Adjustable)

All White	**LRA471W**
All Black	**LRA471B**
All Satin Haze	**LRA471S**
Satin Haze/White	**LRA471SW**

Trim (Frosted Lens Wall Wash)

All White	**LRA472W**
All Black	**LRA472B**
All Satin Haze	**LRA472S**
Satin Haze/White	**LRA472SW**

(For wet locations add -WL)

[1] All drivers are 120V/277V unless otherwise noted.
[2] Warm Dimming only available for 1500lm, 2000lm & 2500lm options.
[3] Tunable White only available with 0-10V signal via "UE-D10P" option or DMX signal via "UE-DMX" option for 2000lm, 3000lm & 3500lm option only.
[4] Check Wiring Diagrams.
[5] Special Order.
[6] (-SUN-RMT) sensor sent with mounting clips for existing ceiling applications.

OPTIONS

/C260
C-Channel Hanger Bar Set

/C260-J
Adjustable C-Channel Hanger Bar Set