



## LRLD35VR : 3.5" P-SERIES




VANDAL RESISTANT ROUND FLANGED 600LM-3000LM (7W-30W)



- New stainless steel vandal resistant rings trim options
- Stainless steel trim/faceplate resists corrosion
- 3/8" tempered glass lens for added resilience
- Silicone gasket creates a watertight seal
- Tamper-resistant stainless steel trim screws for added security
- IK08 rated for impact resistance



Ceiling Cut-Out: 5-1/4"  
Ceiling Thickness: 3/8" Min  
Ceiling Thickness: 1-1/4" Max



[Click for Full Specification Details](#)

Trim	Trim Finish	Lumens	Beam Spread	Color Temperature	Control	Rating	Accessories
<b>Trim Style</b>	<b>FLANGED</b>		<b>Beam Spread</b>		<b>Control</b>	<b>Rating</b>	
Bevel Downlight	<b>LRLD3521VR</b>	600lm (7W)	Wall Wash only <b>Blank<sup>4</sup></b> 15° Beam <b>-B15</b>	2400K (90 CRI) <b>-T24</b> 2700K (97 CRI) <b>-T27</b>	Non-Dimming (120V) <b>Blank</b> TRIAC/ELV Dimming (120V) <b>-DIN</b>	None <b>Blank</b> Airtight Lensed (Wet Location) <b>-WL</b>	
Adjustable Bevel	<b>LRLD3521JVR</b>	1000lm (11W)	24° Beam <b>-B24</b> 36° Beam <b>-B36</b>	2700K (97 CRI) <b>-T27-C97</b> 3000K (90 CRI) <b>-T30</b>	0-10V Dimming (120V/277V) <b>UE-D10</b> 1%, 0-10V Dimming (120V/277V) <b>UE-D10P1</b>	4" J-Box (Chicago Plenum) <b>-JB-CHP</b>	
Adjustable Bevel	<b>LRLD3519VR</b>	1500lm (15W)	50° Beam <b>-B50</b>	3000K (97 CRI) <b>-T30-C97</b> 3500K (90 CRI) <b>-T35</b>	UniDim™ 0-10V, TRIAC/ELV Dimming (120V/277V) <b>UE-DUN</b>		<b>Accessories<sup>7,8</sup></b>
Adjustable Pinhole	<b>LRLD3519JVR</b>	2000lm (21W)		4000K (90 CRI) <b>-T40</b> Dim-to-Warm <b>-TWD<sup>2</sup></b>	Lutron EcoSystem <b>DEC<sup>1</sup></b> Dali Dimming <b>-DLI<sup>1</sup></b>	None <b>Blank</b> Black Hex-Cell Louver <b>-LVR</b>	Red Lens <b>/L39</b> Yellow Lens <b>/L40</b>
Wall Wash	<b>LRLD3573VR</b>	2600lm (25W)		1800K-3000K	Athena Wireless Node (120V) <b>-AWN</b> Casambi Wireless Dimming (120V/277V) <b>-DCSM<sup>1</sup></b> BubbyNet Wireless System (120V/277V) <b>-DBNT<sup>1</sup></b>	BlueRed Lens <b>/L41</b> Amber Lens <b>/L42</b> Green Lens <b>/L43</b> Daylight Blue Lens <b>/L44</b> Violet Blue Lens <b>/L46</b> Frosted Soft Focus <b>/L49</b> Ultra Violet Filter <b>/L50UV</b> Micro Prismatic Spread Lens <b>/L53</b> Linear Spread Lens <b>/L55</b>	
<b>Trim Finish</b>		<b>Lumens</b>					
All Black	<b>B</b>	600lm (7W) <b>-L06</b>					
All White	<b>W</b>	1000lm (11W) <b>-L10</b>					
Custom Color	<b>CC</b>	1500lm (15W) <b>-L15</b>					
		2000lm (21W) <b>-L20</b>					
		2600lm (25W) <b>-L26</b>					
		3000lm (30W) <b>-L30</b>					

<sup>1</sup> Special order, minimum order. Extended lead time may apply. Consult Factory.

<sup>2</sup> (-TWD) is only compatible with (-L15) 1500lm (15W).

<sup>4</sup> Must be selected for Wallwash Trim Style.

<sup>7</sup> Not available with Wall Wash Trim (LRLD3573).

<sup>8</sup> Accessories may not be combined. Limit is one (1) accessory per fixture.

Consult factory for emergency battery options.